



QX Gateways



Features	QXFX04	QXE1T1	QXFXS24
Physical interfaces			
FXO ports	4	N/A	N/A
E1/T1	N/A	1	N/A
FXS ports	N/A	N/A	24
Ethernet RJ-45	2	2	2
Capacity			
Simultaneous IP to PSTN Calls (max)	4	30 (E1)/24 (T1)	24
Call signaling and compression standards			
IP call signaling	SIP	SIP	SIP
PSTN signaling	loop start	CAS, PRI CCS	loop start
Voice coding	G.711, G.726, G.729, iLBC	G.711, G.726, G.729, iLBC	G.711, G.726, G.729, iLBC
Fax	T.38, pass-through fax	T.38, pass-through fax	T.38, pass-through fax
PBX features			
Unconditional call forwarding	yes*	yes*	no
Incoming call blocking	yes*	yes*	no
Outgoing call blocking	yes*	yes*	no
Call waiting	no	no	yes
External voicemail	no	no	yes
T.38 fax relay	yes	yes	yes
Pass-through fax	yes	yes	yes
Auto Attendant	yes	yes	no
Zero-Out for Auto Attendant	yes	yes	no

*Can be configured based on caller ID per each extension

Features	QXFX04	QXE1T1	QXFXS24
PBX features continued			
Auto Attendant call back for SIP callers	yes	yes	no
Auto Attendant call back for PSTN callers	yes	yes	no
Call redirection on Auto Attendant	yes	yes	no
Auto Attendant ringing announcement	yes	yes	no
Authorized phone database	yes	yes	no
Multi-level IVR	yes	yes	no
Configurable call routing	yes	yes	yes
Date/time based routing	yes	yes	yes
Routing with call duration limit	yes	yes	yes
Overall call duration limit per routing entry	yes	yes	yes
Global speed dialing	yes	yes	yes
Call history	yes	yes	yes
Automatic downloading of call history	yes	yes	yes
SIP tunneling	yes	yes	yes
Gateway Hosted Survivability	yes**	yes**	N/A

Note: Most of ecQX and QX/UC PBX features are available on QXFXS24 in shared mode.

Network			
Stateful inspection firewall	yes	yes	yes
Policy and service filtering	yes	yes	yes
Integrated NAT	yes	yes	yes

** The HS feature is enabled by installing a software license key

Features	QXFX04	QXE1T1	QXFXS24
Network continued			
LAN DHCP server	yes	yes	yes
WAN DHCP client	yes	yes	yes
STUN/NAT traversal	yes	yes	yes
VPN	yes	yes	yes
OpenVPN	no	no	yes
VLAN	yes	yes	yes
TLS	yes	yes	yes
SRTP	yes	yes	yes
SNTP	yes	yes	yes
SMTP	yes	yes	yes
SNMP	yes	yes	yes
IDS	yes	yes	yes
SIP IDS	yes	yes	yes
PPPoE	yes	yes	yes
DNS server	yes	yes	yes
DYNDNS support	yes	yes	yes
TOS/DIFFSERV	yes	yes	yes

Management			
HTTP/HTTPS access to GUI	yes	yes	yes
Local admin	yes	yes	yes
Password control	yes	yes	yes
Multi-language support	yes	yes	yes
Plug-and-Play (PnP) with QX IP PBXs	no	no	yes

Features	QXFX04	QXE1T1	QXFXS24
Management continued			
PSTN trunk/line sharing with QX IP PBXs	yes	yes	N/A
Radius	yes	yes	yes
Network capture	yes	yes	yes
Call capture	yes	yes	yes
Remote testing	yes	yes	yes
System configuration automatic backup and download	yes	yes	yes
Legible configuration	yes	yes	yes
Configuration download/restore	yes	yes	yes
IDS logs	yes	yes	yes
System logs	yes	yes	yes
System event notification via SMS/email	yes	yes	yes
System security diagnostics and audit	yes	yes	yes
System status	yes	yes	yes
Automatic firmware update	yes	yes	yes

THIS DOCUMENT IS PROVIDED TO YOU FOR INFORMATIONAL PURPOSES ONLY. The information furnished in this document, believed by Epygi Technologies to be accurate as of the date of publication, is subject to change without notice. Epygi Technologies assumes no responsibility for any errors or omissions in this document and shall have no obligation to you as a result of having made this document available to you or based upon the information it contains.

Epygi, Quadro and QX are registered trademark of Epygi Technologies, LLC. All other products and services are the registered trademarks of their respective holders.